



| | 1505 | 1506 | 1507 |
|------------------------|--------------|----------------|-----------------------|
| PTO HP | 35-80 | 40-80 | 55-95 |
| WIDTH | 60" | 72" | 84" |
| WEIGHT | 745 LBS | 900 LBS | 1305 LBS |
| CUTTING CAPACITY | 2.5" | 2.5" | 3" |
| DECK THICKNESS | 10 GA | 10 GA | 10 GA |
| SIDE BANDS | 7" | 7" | 8" |
| PTO DRIVE SHAFT | SERIES 4 | SERIES 4 | SERIES 6 |
| STUMP JUMPER | 1/2" PLATE | 1/2" PLATE | 5/8" PLATE |
| GEAR BOX | 100 HP | 100 HP | 150 HP |
| TAILWHEELS | 1 | 1 | 2 |
| WHEEL | LAMINATED | LAMINATED | LAMINATED |
| HUB | GREASABLE | GREASABLE | GREASABLE BEARING HUB |
| HITCH | CAT 1 | CAT 1 | CAT 2 |
| QUICK HITCH COMPATIBLE | YES | YES | YES CAT 2 |
| GEARBOX WARRANTY | 5 YR LIMITED | 5 YEAR LIMITED | 5 YEAR LIMITED |
| DISCHARGE SHIELDS | AVAILABLE | AVAILABLE | AVAILABLE |

1500 SERIES CUTTER

These rotary cutters are designed for medium/heavy-duty applications such as weeds, grass, and brush up to 2.5" or 3" diameter, depending on model. These cutters are designed to work with 35 to 95 horsepower tractors, and are available in 60", 72" and 84" widths.

These cutters use a single spindle with two free-swinging blades, which reduce the shock of impact when a stationary object is contacted. Standard equipment includes driveline shields and clutch shields. Front and rear chain discharge shields are optional. Front and rear belting available for the 1506 or 1507 Cutters.

COLOR OPTIONS

