

1912 FLEX-WING ROTARY CUTTER

Brush Chief



COLOR OPTIONS



1912 FLEX-WING ROTARY CUTTER

With a smooth top deck and spring suspension, this Flex-Wing Rotary Cutter is ideal for medium duty applications such as weeds, grass and brush up to 2" diameter. Designed for use with compact tractors as small as 35 horsepower.

The cutter requires only one hydraulic outlet for its 144" cut width. The cutter uses three independent spindles with two free-swinging blades each, to reduce the shock of hitting a stationary object. Slip clutches protect the gearboxes and drivelines from damage. Standard equipment includes driveline shields, clutch shields, chain discharge shields and a towing safety chain.



Brush Chief

1912

FLEX-WING ROTARY CUTTER

	1912		1912
RECOMMENDED MINIMUM PTO HP	35 HP (GEAR DRIVE TRANS)	CUT WIDTH	144"
HITCH	SWIVEL CLEVIS	OVERALL WIDTH	151"
DECK THICKNESS	10 GAGE	OVERALL LENGTH W/WHEELS	158"
DECK HEIGHT	11"	TONGUE WEIGHT	759 LBS
SIDE SKIT MATERIAL	3/16"	OVERALL WEIGHT	2630 LBS
HINGE RODS	1"	CUT HEIGHT	1-1/2"-12"
SUSPENSION	SINGLE SPRING	CUTTING CAPACITY	UP TO 2"
OUTBOARD GEARBOX PWR RATING	75 HP	INPUT PTO	ASAE CAT 5 CONSTANT VELOCITY
SPLITTER GEARBOX PWR RATING	175 HP	WING DRIVE PTO	ASAE CAT 4 w/SLIP CLUTCH
GEARBOX RPM	540 RPM	SKID SHOES	REPLACEABLE
BLADES	1/2" X 3" w/LIFT	CHAIN SHIELDS	SINGLE ROW CHAIN SHIELDS STANDARD
BLADE TIP SPEED	15,657 FPM	TOWING SAFETY CHAIN	STANDARD
BLADE OVERLAP	6"	GEARBOX WARRANTY	5 YR LIMITED
BLADE CARRIERS	ROUND PAN	WHEEL TYPE	5 LUG LAMINATED STD-USED AIRCRAFT TIRES OPTIONAL
BLADE CARRIERS	3/16" FORMED PLATE w/ 3/4 x2-" BLADE BAR		